

BOGE C-2 series

Compact. Efficient. Quiet.



TECHNICAL DATA

BOGE type	Max. pressure	Effective free air delivery	Motor power	Dimensions	Compressed-air outlet	Sound pressure level super sound insulation	Weight with super sound insulation
	bar	m³/min	kW	W x D x H (mm)		dB(A)	kg
C 12-2	7.5	1.97	11	1610 x 915 x 1380	G 1"	63	522
C 12-2	10	1.76	11	1610 x 915 x 1380	G 1"	63	522
C 12-2	13	1.31	11	1610 x 915 x 1380	G 1"	63	522
C 12-2	15	1.08	11	1610 x 915 x 1380	G 1"	63	522
C 12-2 L	7.5	1.82	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 L	10	1.80	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	7.5	0.53 - 2.02	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	10	0.52 - 1.76	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	13	0.51 - 1.31	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	15	0.46 - 1.15	11	1610 x 915 x 1380	G 1"	63	557
C 15-2	7.5	2.56	15	1610 x 915 x 1380	G 1"	65	532
C 15-2	10	2.25	15	1610 x 915 x 1380	G 1"	65	532
C 15-2	13	1.89	15	1610 x 915 x 1380	G 1"	65	532
C 15-2	15	1.53	15	1610 x 915 x 1380	G 1"	65	532
C 15-2 L	7.5	2.26	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 L	10	2.22	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	7.5	0.53 - 2.63	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	10	0.52 - 2.27	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	13	0.51 - 1.89	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	15	0.48 - 1.52	15	1610 x 915 x 1380	G 1"	65	557
C 18-2	7.5	3.12	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2	10	2.71	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2	13	2.32	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2	15	2.10	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	7.5	0.54 - 3.19	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	10	0.52 - 2.75	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	13	0.72 - 2.32	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	15	0.71 - 2.06	18.5	1610 x 915 x 1380	G 1"	68	567
C 22-2	7.5	3.64	22	1610 x 915 x 1380	G 1"	69	597
C 22-2	10	3.21	22	1610 x 915 x 1380	G 1"	69	597
C 22-2	13	2.74	22	1610 x 915 x 1380	G 1"	69	597
C 22-2	15	2.47	22	1610 x 915 x 1380	G 1"	69	597
C 22-2 LF	7.5	0.54 - 3.73	22	1610 x 915 x 1380	G 1"	69	602
C 22-2 LF	10	0.52 - 3.27	22	1610 x 915 x 1380	G 1"	69	602
C 22-2 LF	13	0.72 - 2.74	22	1610 x 915 x 1380	G 1"	69	602
C 22-2 LF	15	0.70 - 2.48	22	1610 x 915 x 1380	G 1"	69	602

BOGE C-2 series

Compact. Efficient. Quiet.



TECHNICAL DATA

BOGE type	With dryer (D)		With 500 l receiver (R)		With 500 l receiver and dryer (DR)	
	Dimensions	Weight super sound insulation	Dimensions	Weight super sound insulation	Dimensions	Weight super sound insulation
	W x D x H (mm)	kg	W x D x H (mm)	kg	W x D x H (mm)	kg
C 12-2 _ C 15-2	1610 x 915 x 1380	562 / 582	2036 x 915 x 1915	673 / 683	2036 x 915 x 1915	713 / 733
C 12-2 L _ C 15-2 L	1610 x 915 x 1380	557 / 567	2036 x 915 x 1915	668	2036 x 915 x 1915	708 / 718
C 12-2 LF _ C 15-2 LF	1610 x 915 x 1380	597	2036 x 915 x 1915	708 / 698	2036 x 915 x 1915	748
C 18-2 _ C 22-2	1610 x 915 x 1380	617 / 647	2036 x 915 x 1915	718 / 748	2036 x 915 x 1915	768 / 798
C 18-2 LF _ C 22-2 LF	1610 x 915 x 1380	617 / 652	2036 x 915 x 1915	718 / 753	2036 x 915 x 1915	768 / 803